




1. MANUFACTURER

Roppe Corporation

1602 N. Union Street
P.O. Box 1158
Fostoria, Ohio USA 44830-1158
t: (419) 435.8546 | tf: (800) 537.9527
f: (419) 435.1056
E-mail: sales@roppe.com
Internet: www.roppe.com

2. PRODUCT DESCRIPTION

Low cost and good looks highlight Roppe's Type TV thermoplastic vinyl base. It's extremely durable without sacrificing attractiveness and very economical because it's made from PVC vinyl.



Standard Toe:
For many installations.

Profile: Standard Cove

Gauge: 0.080" (2 mm) or 1/8" (3.2 mm)

Heights: 2 1/2" (63.5 mm), 4" (101.6 mm) or 6" (152.4 mm)

Lengths: 48" (1.22 m) Pieces & 120' (36.58 m) Coils

Factory Corners: Inside & Outside Corners in 2 1/2" (63.5 mm), 4" (101.6 mm), 6" (152.4 mm) heights with 3" (76.2 mm) returns

3. TECHNICAL DATA

ASTM F 1861 - Type TV, Group 1, Style B

ASTM E 648, Critical Radiant Flux - Class 1 >.45 W/cm²

ASTM E 662, Smoke Density - Passes <450

ASTM E 84, Surface Burning - Class B

According to the BOCA (Building Officials & Code Administrators International Inc.) codes and the NFPA (National Fire Protection Agency), Accessories are considered incidental trim. According to these sections, any incidental trim not in excess of 10% of the aggregate wall and ceiling area of any room or space may be Class C material in occupancies where interior finish of Class A or Class B is required.

4. LIMITATIONS

Roppe Vinyl Wall Base is for indoor use only. Do not install on any surface exposed to moisture or extreme temperature changes. Do not install in areas subject to vegetable or petroleum based oils & greases. Fading can occur from extensive exposure to heavy direct or glass-filtered sunlight, or unfiltered ultra-violet rays.

5. INSTALLATION

Adhesive for Porous Substrates

1100 Wall Base Adhesive is a premium solvent free Acrylic adhesive with aggressive wet suction grip for all Roppe Wall Base products. Coverages are described on the 1100 Wall Base Adhesive quick spec.

Adhesive for Non-Porous Substrates

Use a premium contact adhesive for installation over all non-porous substrates such as metal, FRP panels, etc.

6. MAINTENANCE

Clean base with neutral pH cleaner and a soft wet cloth

7. AVAILABILITY AND COST

Products are available through Roppe distributors. Contact Roppe Customer Service (800) 537-9527 or visit www.roppe.com.

8. TECHNICAL ASSISTANCE

Technical service information and assistance may be obtained by calling Roppe Customer Service at 1-800-537-9527, or by visiting www.roppe.com.

9. SAMPLES

Obtain samples by calling Roppe Customer Service at 1-800-537-9527, or by visiting www.roppe.com.

10. LIMITED WARRANTY

Limited two (2) Year Manufacturer's Warranty

For complete substrate preparation, installation and/or maintenance instructions please visit www.roppe.com

